

(19) 世界知的所有権機関
国際事務局



(43) 国際公開日
2001 年 10 月 4 日 (04.10.2001)

PCT


(10) 国際公開番号
WO 01/73216 A1

- (51) 国際特許分類: E02F 9/16 (71) 出願人 (米国を除く全ての指定国について): 日立建機株式会社 (HITACHI CONSTRUCTION MACHINERY CO., LTD.) [JP/JP]; 〒112-0004 東京都文京区後楽二丁目5番1号 Tokyo (JP).
- (21) 国際出願番号: PCT/JP01/02529
- (22) 国際出願日: 2001 年 3 月 28 日 (28.03.2001) (72) 発明者: および
- (25) 国際出願の言語: 日本語 (75) 発明者/出願人 (米国についてのみ): 左京 剛 (SAKYO, Tsuyoshi) [JP/JP]; 〒315-0052 茨城県新治郡千代田町下稲吉2645-64 Ibaraki (JP).
- (26) 国際公開の言語: 日本語 (74) 代理人: 影井俊次 (KAGEI, Toshitsugu); 〒160-0023 東京都新宿区西新宿1丁目9番12号 第一大正建物ビル4階 Tokyo (JP).
- (30) 優先権データ: 特願2000-089171 2000 年 3 月 28 日 (28.03.2000) JP (81) 指定国 (国内): CN, KR, US.
- 28 Nov 01

[続葉有]

(54) Title: CABIN OF CONSTRUCTION MACHINERY

(54) 発明の名称: 建設機械の運転室



(57) Abstract: A cabin (10) of construction machinery disposed on an upper structure (2) having a front working machine installed thereon, comprising a first side structural body (11) having an openable door (20) provided thereon, a second side structural body (12) disposed at a position adjacent to the front working machine (7), a front part (13) provided between both side structural bodies (11) and (12) and having a front window (23) generally on the entire surface thereof, a roof part (15), and a rear surface part (14), wherein a lateral rail (26) is provided at the upper position of the front window (23) and a reinforcing member (30) for reinforcing the lateral rail (23) is installed across the first and second side structural bodies (11) and (12).

[続葉有]

09953792660

WO 01/73216 A1

ABRIDGEMENT

A cab 10 is provided on an upper rotary body 2 of a construction machine along with a front working mechanism 7. The cab 10 provides an operating room within an enclosure which mainly consists a first side frame structure 11 containing a door to be opened and closed by an operator, a second side frame structure 12 located on the side of the front working mechanism 7, a front section 13 provided between front ends of the first and second side frame structures 11 and 12 and substantially entirely occupied by a front window 23, a roof section 15 and a rear section 14. In addition to a cross beam member 26 which is bridged between upper front corner portions of the first and second side frame structures 11 and 12, a reinforcing the cross beam member 26 is bridged alongside the cross beam member 26 for reinforcing same.